



Permastop®

Thermal, Acoustic and Condensation Control
for **Metal Roofs**

Product **application**

Suitable for commercial metal roofs and residential metal roofs, including homes and sheds.

Fire safe

- Meets AS1530.3 (0,0,0,1)
- Glasswool component meets AS/NZS1530.1 for Non-Combustibility
- Sisalation® Reflective Foil facing component meets BCA flammability index requirement of ≤ 5

Thermal Certification

According to AS/NZS 4859.1



Acoustic control



Condensation control



Fire resistance



Thermal performance

Permastop® Features and Benefits

Combines two effective types of insulation to offer on product solution.	Saves time and costs toward your overall construction project.
Reduces the risk of condensation forming under metal roofs.	Prevents damage to ceilings often caused by the development of mould.
Assists in heavily reducing unwanted external noise inside a building often caused by weather conditions.	Provides a more comfortable living and working space.
Delivers overall building energy efficiency keeping buildings cool in summer and warm in winter.	Reduces future ongoing costs on energy bills and unnecessary stress on HVAC systems.
Custom cut lengths available.	Reduces waste and install time.
Available in a range of thicknesses.	Effectively meet the NCC 2019 Energy Efficiency Provision.
Environmentally positive made from up to 85% recycled material.	Minimal impact on the environment.

Duty selection for metal roof (4200.2 Allowable Usage in Australia)

Climate	Span mm	Duty		Product
		Supported	Unsupported	
Standard	≤900	Light Duty	Light Duty	Permastop® Building Blanket LD
	>900 to ≤1200	Light Duty	Medium Duty	
		Medium Duty	*	Permastop® Building Blanket MD
	>1200	Heavy Duty	Heavy Duty	
		Extra Heavy Duty	Extra Heavy Duty	
Tropical/hot/high humidity	≤900	Light Duty	Light Duty	Permastop® Tropic Building Blanket LD
	>900 to ≤1200	Light Duty	Medium Duty	
		>1200	Medium Duty	*



© Fletcher Insulation Pty Limited 2020. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Unless otherwise stated all ™ and © are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. FL0015_Revision_0_Issue Date 29042020.



ROOFING & PROFILES (FIJI) PTE LTD
Build With Confidence

Fletcher
Insulation
 Building Better, Together