



RPFL 0.55 BMT RIDGE CAP
 Base Materials: coating AZ200 Steel Grade G300.
 fixed to the roof cladding with
 SDM/TIMBER Screw / silicon sealant
 and rivet together .

RPFL SuperDek® Colorbond® XRW/Ultra
 0.42BMT/0.48BMT roof cladding.
 Base Materials: Steel Grade G550.
 BMT 0.42.Mass 4.3kg/m2 or 0.48BMT 4.9kg/m2.
 AZ 150 coating for XRW & AZ 200 coating for Ultra.
 Profiles tested for Cyclonic Conditions.

Kingspan AIR-CELL INSULINER Self-Supported
 3-in-1 Insulation Vapour Barrier and Radiant Barrier
 or 430 WF Med. duty sisalation

Aushmesh 300 Galvanized roof safety mesh
 Wire mesh 1.8 X 50m(90m2/roll) Mesh gap
 300 X 150mm

Structure as per engineers details

Notes:
 All installation to be as per New Zealand steel
 specification and installation guide. (March 2011)
 & New Zealand roof and cladding
 CODE OF PRACTICE (Version 2.2/2012)



Roofing & Profiles (Fiji) Pte Ltd
 Ph: (679) 6673764 M: 999 9309
 Email: info@roofingandprofiles.com.fj

This drawing is the property of Roofing &
 Profiles (Fiji) Pte Ltd and must not be copied
 or disclosed to any third party without the
 written consent of the company.
 ALL DIMENSIONS ARE IN mm UNLESS
 STATED

PROJECT TITLE:
ROOF DETAILS

DRAWING TITLE:
SHOP DRAWINGS

DRAWN: CVB
 DATE : 15/12/2020
 CHECKED BY:

SCALE: 1:5 @ A4
 REVISION No:
 APPROVED BY:

SHEET No : SD 1090
 REVISION TITLE:
 JOB NUMBER: 13 - RAIN