

Kingspan AIR-CELL INSULINER Self-Supported  
3-in-1 Insulation Vapour Barrier and Radiant Barrier  
or 430 WF Med. duty sisalation.

Aushmesh 300 Galvanized roof safety mesh  
Wire mesh 1.8 X 50m(90m2/roll) Mesh gap  
300 X 150mm

RPFL Std Colorbond® XRW/Ultra 0.55 BMT Flashing  
Base Materials: coating AZ200 Steel Grade G300.  
fixed to the roof cladding with SDM Screw.

RPFL SuperDek®/Corrudek Colorbond® XRW/Ultra  
0.42BMT/0.48BMT Ceiling cladding. Base Materials: Steel  
Grade G550. BMT 0.42.Mass 4.3kg/m2 or 0.48BMT  
4.9kg/m2. AZ 150 coating for XRW & AZ 200 coating for  
Ultra. Profiles tested for Cyclonic Conditions.

RPFL Std Colorbond® XRW/Ultra 0.55 BMT Flashing  
Base Materials: coating AZ200 Steel Grade G300.  
fixed to the roof cladding with SDM Screw.

RPFL SuperDek®/Corrudek Colorbond® XRW/Ultra  
0.42BMT/0.48BMT Wall cladding. Base Materials: Steel  
Grade G550. BMT 0.42.Mass 4.3kg/m2 or 0.48BMT  
4.9kg/m2. AZ 150 coating for XRW & AZ 200 coating for  
Ultra. Profiles tested for Cyclonic Conditions.

**Notes:**

All installation to be as per New Zealand steel  
specification and installation guide. (March 2011)  
& New Zealand roof and cladding  
CODE OF PRACTICE ( Version 2.2/2012 )

130mm min. medium wind speed areas or  
pitches greater than 10°  
200mm min. high wind speed areas and  
higher or pitches below 10°

